



NET4GAS, s.r.o

HP PIPELINE DN 1400, NODE KATEŘINSKÝ POTOK – NODE PŘIMDA

Ball Valves with Combined Sealing \geq DN 300 Datasheet

30.07.2018

DVZ

ILF CONSULTING ENGINEERS

Werner-Eckert-Strasse 7, 81829 München, DE
Jirsíkova 5, 186 00 Praha 8, CZ

Phone: +49 89 25 55 94-0

+420 255 091 420

E-mail: info.muc@ilf.com

info.prg@ilf.com

Website: www.ilf.com



REVISION HISTORY

002	30.07.2018	Re-Approved	Mustafa	Balatinec	Schorling
001	26.06.2018	Re-Approved	Mustafa	Balatinec	Schorling
000	12.06.2018	Approved	Mustafa	Balatinec	Schorling
B01	03.05.2018	Issue for Review	Mustafa	Balatinec	Schorling
A01	20.04.2018	Issue for IDC	Mustafa	Balatinec	Schorling
Rev.	Date	Issue, Purpose	Prepared	Checked	Approved

TABLE OF CONTENTS

PAGE	TYPE OF VALVE	SIZE
LVS JIRKOV (Note 1)		
4	Ball Valve – Electro Motor (MOV-7.3, MOV-7.4)	DN 500
LVS VRSKMAN (Note 1)		
5	Ball Valve – Electro Motor (MOV-7.10, MOV-7.11)	DN 500
LVS HRUSOVANY		
6	Ball Valve – Electro Motor (MOV-7.3, MOV-7.4)	DN 500
LVS SYROVICE		
7	Ball Valve – Electro Motor (MOV-7.3, MOV-7.4)	DN 500
LVS MALMERICE		
8	Ball Valve – Gas Hydraulic (GHV-2.3)	DN 1200
9	Ball Valve – Electro Motor (MOV-7.5, MOV-7.6, MOV-7.7, MOV-7.8)	DN 500
10	Ball Valve – Electro Motor (MOV-8.10, MOV-8.12)	DN 300
11	Ball Valve – Electro Motor (MOV-8.11, MOV-8.13)	DN 300
12	Ball Valve – Manual (MOV-8.14)	DN 300
LVS MLADOTICE		
13	Ball Valve – Electro Motor (MOV-7.3, MOV-7.4)	DN 500
LVS HUBENOV		
14	Ball Valve – Electro Motor (MOV-7.3, MOV-7.4)	DN 500
LVS SVINOMAZY		
15	Ball Valve – Electro Motor (MOV-7.25, MOV-7.26)	DN 500
LVS BOR		
16	Ball Valve – Electro Motor (MOV-7.3, MOV-7.4)	DN 500
RU PRIMDA		
17	Ball Valve – Electro Motor (MOV-8.33)	DN 300
18	Ball Valve – Manual (MOV-8.34)	DN 300

Note 1: LVS Jirkov is alternative location to LVS Vrskman. Only one LVS of those two stations shall be constructed, either Jirkov or Vrskman.

BALL VALVE - DN 500

1	GENERAL INFORMATION				
2	LOCATION	LVS JIRKOV	5	QUANTITY	2 (Note 6)
3	EQUIPMENT	BALL VALVE	6	TECHNICAL SPECIFICATION	C4G-HPPL-ILF-GENER-STR-SPC-824
4	TAG No.	MOV-7.3, MOV-7.4	7	P&ID-No.	C4G-HPPL-ILF-TU33S-STR-DIA-110
8	OPERATION AND DESIGN DATA				
9	AMBIENT CONDITIONS	C4G-HPPL-ILF-GENER-GEN-SPC-901	16	MAX. OPERATING PRESSURE	85 barg
10	MEDIUM	NATURAL GAS	17	OPERATING TEMPERATURE	+5 to +25 °C
11	GAS COMPOSITION	C4G-HPPL-ILF-GENER-GEN-DAT-820	18	DESIGN PRESSURE	100 barg
12	PIPING CLASS	CS100-0	19	DESIGN TEMPERATURE	-20 to +50 °C
13	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	20	TEST PRESSURE	150 barg
14	FLANGE STANDARD / RATING	N/A	21	SAFETY FACTOR (TO YIELD POINT)	2.15
15	INSTALLATION	ABOVEGROUND	22	SAFETY FACTOR ON WELD ENDS (TO YIELD POINT)	1.68
23	VALVE DATA				
24	VALVE BODY / BALL DESIGN	FULLY WELDED BODY	36	SUPPORT LEGS	YES
25	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	37	LIFTING LUGS	YES
26	NOMINAL PIPE SIZE / OD / THICKNESS	DN 500 / 508 mm / 12.5 mm	38	FLOW DIRECTION	BIDIRECTIONAL
27	PIPELINE CONNECTION TYPE	WELD / WELD	39	LEAK RATE	ACC. TO EN 12266-1, -2; RATE A
28	MAIN SEALS	METAL	40	MAX. VALVE LIFT	*
29	SECONDARY SEALS	SOFT	41	STEM DIAMETER / TYPE	* / ANTI-BLOW-OUT
30	SEATS RINGS	DOUBLE PISTON EFFECT	42	LOCK POSITION	YES
31	CAVITY PRESSURE RELIEF VALVE	N/A	43	ADJUSTABLE LIMIT STOP	*
32	DOUBLE BLOCK & BLEED	YES	44	ANTI STATIC DESIGN	YES
33	VENT	YES	45	FIRE SAFE DESIGN	YES
34	DRAIN	YES	46	SEALANT LINE INJECTION MEDIA	4 INDPEDENT GREASE FITTINGS
35	INSULATION	NO	47		
48	ACTUATOR AND ACCESSORIES				
49	ACTUATOR TYPE	ELECTRO MOTOR (Note 2) (Note 7)	61	STROKING TIME TO OPEN (Min./Max.)	40 s/180 s
50	MANUFACTURER/ MODEL	AUMATIC SAEx	62	STROKING TIME TO CLOSE (Min./Max.)	60 s /180 s
51	GEAR BOX WITH HANDWHEEL	N/A	63	LIMIT SWITCH	YES
52	DESIGN TORQUE FOR ACTUATOR	*	64	POSITIONER MANUFACT / MODEL	*
53	ACTUATOR ATTACHMENT	ACC. TO EN ISO 5211	65	STEM	*
54	FAIL SAFE POSITION	N/A	66	STEM EXTENSION FOR UNDERGROUND	VALVE CL TO ACTUATOR FLANGE
55	POWER SUPPLY	400V / 50 Hz / 3 Ph	67	INSTALLATION	VALVE CL TO GROUND LEVEL
56	IP-CODE	IP 65 (IEC 60529)	68	BY-PASS AND AIR-BLEED VALVE	N/A
57	INSULATING CLASS	I	69	OIL AND GAS FILTERS	N/A
58	HAZARDOUS AREA	ZONE 1	70	CONTROL UNIT	C4G-HPPL-ILF-GENER-STR-SPC-824
59	EXPLOSION PROTECTION	II 2G IIB T3	71	ACTUATOR LOCKING	SELF LOCKING
60	MINIMUM SUPPLY PRESSURE	N/A	72	MECHANICAL POSITION INDICATOR	YES - OPEN/CLOSE
73	DIMENSIONS, WEIGHT, MECHANICAL AND ELECTRICAL INTERFACES				
74	FITTING LENGTH	*	78	WEIGHT (VALVE)	*
75	FITTING HEIGHT	*	79	WEIGHT (VALVE + ACTUATOR)	*
76	WALL THICKNESS	*	80	CABLE CONNECTION TYPE	Exd Cable Gland
77			81	CABLE CONNECTION SIZE	*
82	MATERIALS, TESTING AND DOCUMENTATION				
83	MATERIAL OF PIPE END	L360NE	92	STANDARD TEST	ACC TO CSN EN 14141 / API 6D
84	VALVE MATERIAL	ACC. TO ČSN EN 1594/API 6D	93	LEAKAGE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
85	BALL MATERIAL	C4G-HPPL-ILF-GENER-STR-SPC-824	94	PRESSURE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
86	PUP PIECES MATERIAL	*	95	TIGHTNESS TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
87	MATERIAL STEM	*	96	FIRE SAFE TEST	ACC. TO API 607 / ISO 10497
88	MATERIAL BOLTS / NUTS	ACC. TO ČSN EN ISO 898	97	ATEX CERTIFICATION	ACC. TO CSN EN 60079-10
89	MATERIAL SEAT / SEAL	A350 LF2 / HNBR (Therban) *	98	SAFETY INTEGRITY LEVEL	N/A
90	ANTI - CORROSION PROTECTION	C4G-HPPL-ILF-GENER-STR-SPC-824	99	FINAL ACCEPTANCE TEST	ČSN EN 10204 / 3.2
91	DOCUMENTATION	C4G-HPPL-ILF-GENER-STR-SPC-824	100	CE-CONFORMITY	ACC. TO PED 2014/68/EU
101	NOTES				
102	* To be filled/confirmed by Supplier				
103	Note 1: This data sheet shall be read with the Specification C4G-HPPL-ILF-GENER-STR-SPC-824				
104	Note 2: Motor Operated Valve (MOV) with Local and Remote Control and Monitoring Functionality				
105	Note 3: CL - Center Line				
106	Note 4: N/A - Not Applicable				
107	Note 5: Control and Signaling Voltage 24 VDC				
108	Note 6: LVS Jirkov is alternative location to LVS Vrskman. Only one LVS of those two stations shall be constructed, either Jirkov or Vrskman				
109	Note 7: The type of wiring diagram shall be "TPCAA121D1H1-E460 TPA00R200-012-000"				
110					
111					
112					
113					
114					
115					
116					
117					

BALL VALVE - DN 500

1	GENERAL INFORMATION				
2	LOCATION	LVS VRSKMAN	5	QUANTITY	2 (Note 6)
3	EQUIPMENT	BALL VALVE	6	TECHNICAL SPECIFICATION	C4G-HPPL-ILF-GENER-STR-SPC-824
4	TAG No.	MOV-7.10, MOV-7.11	7	P&ID-No.	C4G-HPPL-ILF-KS07B-STR-DIA-110
8	OPERATION AND DESIGN DATA				
9	AMBIENT CONDITIONS	C4G-HPPL-ILF-GENER-GEN-SPC-901	16	MAX. OPERATING PRESSURE	85 barg
10	MEDIUM	NATURAL GAS	17	OPERATING TEMPERATURE	+5 to +25 °C
11	GAS COMPOSITION	C4G-HPPL-ILF-GENER-GEN-DAT-820	18	DESIGN PRESSURE	100 barg
12	PIPING CLASS	CS100-0	19	DESIGN TEMPERATURE	-20 to +50 °C
13	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	20	TEST PRESSURE	150 barg
14	FLANGE STANDARD / RATING	N/A	21	SAFETY FACTOR (TO YIELD POINT)	2.15
15	INSTALLATION	ABOVEGROUND	22	SAFETY FACTOR ON WELD ENDS (TO YIELD POINT)	1.68
23	VALVE DATA				
24	VALVE BODY / BALL DESIGN	FULLY WELDED BODY	36	SUPPORT LEGS	YES
25	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	37	LIFTING LUGS	YES
26	NOMINAL PIPE SIZE / OD / THICKNESS	DN 500 / 508 mm / 12.5 mm	38	FLOW DIRECTION	BIDIRECTIONAL
27	PIPELINE CONNECTION TYPE	WELD / WELD	39	LEAK RATE	ACC. TO EN 12266-1, -2; RATE A
28	MAIN SEALS	METAL	40	MAX. VALVE LIFT	*
29	SECONDARY SEALS	SOFT	41	STEM DIAMETER / TYPE	* / ANTI-BLOW-OUT
30	SEATS RINGS	DOUBLE PISTON EFFECT	42	LOCK POSITION	YES
31	CAVITY PRESSURE RELIEF VALVE	N/A	43	ADJUSTABLE LIMIT STOP	*
32	DOUBLE BLOCK & BLEED	YES	44	ANTI STATIC DESIGN	YES
33	VENT	YES	45	FIRE SAFE DESIGN	YES
34	DRAIN	YES	46	SEALANT LINE INJECTION MEDIA	4 INDPEDENT GREASE FITTINGS
35	INSULATION	NO	47		
48	ACTUATOR AND ACCESSORIES				
49	ACTUATOR TYPE	ELECTRO MOTOR (Note 2) (Note 7)	61	STROKING TIME TO OPEN (Min./Max.)	40 s/180 s
50	MANUFACTURER/ MODEL	AUMATIC SAEx	62	STROKING TIME TO CLOSE (Min./Max.)	60 s /180 s
51	GEAR BOX WITH HANDWHEEL	N/A	63	LIMIT SWITCH	YES
52	DESIGN TORQUE FOR ACTUATOR	*	64	POSITIONER MANUFACT / MODEL	*
53	ACTUATOR ATTACHMENT	ACC. TO EN ISO 5211	65	STEM	*
54	FAIL SAFE POSITION	N/A	66	STEM EXTENSION FOR UNDERGROUND	VALVE CL TO ACTUATOR FLANGE
55	POWER SUPPLY	400V / 50 Hz / 3 Ph	67	INSTALLATION	VALVE CL TO GROUND LEVEL
56	IP-CODE	IP 65 (IEC 60529)	68	BY-PASS AND AIR-BLEED VALVE	N/A
57	INSULATING CLASS	I	69	OIL AND GAS FILTERS	N/A
58	HAZARDOUS AREA	ZONE 1	70	CONTROL UNIT	C4G-HPPL-ILF-GENER-STR-SPC-824
59	EXPLOSION PROTECTION	II 2G IIB T3	71	ACTUATOR LOCKING	SELF LOCKING
60	MINIMUM SUPPLY PRESSURE	N/A	72	MECANICAL POSITION INDICATOR	YES - OPEN/CLOSE
73	DIMENSIONS, WEIGHT, MECHANICAL AND ELECTRICAL INTERFACES				
74	FITTING LENGTH	*	78	WEIGHT (VALVE)	*
75	FITTING HEIGHT	*	79	WEIGHT (VALVE + ACTUATOR)	*
76	WALL THICKNESS	*	80	CABLE CONNECTION TYPE	Exd Cable Gland
77			81	CABLE CONNECTION SIZE	*
82	MATERIALS, TESTING AND DOCUMENTATION				
83	MATERIAL OF PIPE END	L360NE	92	STANDARD TEST	ACC TO CSN EN 14141 / API 6D
84	VALVE MATERIAL	ACC. TO ČSN EN 1594/API 6D	93	LEAKAGE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
85	BALL MATERIAL	C4G-HPPL-ILF-GENER-STR-SPC-824	94	PRESSURE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
86	PUP PIECES MATERIAL	*	95	TIGHTNESS TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
87	MATERIAL STEM	*	96	FIRE SAFE TEST	ACC. TO API 607 / ISO 10497
88	MATERIAL BOLTS / NUTS	ACC. TO ČSN EN ISO 898	97	ATEX CERTIFICATION	ACC. TO CSN EN 60079-10
89	MATERIAL SEAT / SEAL	A350 LF2 / HNBR (Therban) *	98	SAFETY INTEGRITY LEVEL	N/A
90	ANTI - CORROSION PROTECTION	C4G-HPPL-ILF-GENER-STR-SPC-824	99	FINAL ACCEPTANCE TEST	ČSN EN 10204 / 3.2
91	DOCUMENTATION	C4G-HPPL-ILF-GENER-STR-SPC-824	100	CE-CONFORMITY	ACC. TO PED 2014/68/EU
101	NOTES				
102	* To be filled/confirmed by Supplier				
103	Note 1: This data sheet shall be read with the Specification C4G-HPPL-ILF-GENER-STR-SPC-824				
104	Note 2: Motor Operated Valve (MOV) with Local and Remote Control and Monitoring Functionality				
105	Note 3: CL - Center Line				
106	Note 4: N/A - Not Applicable				
107	Note 5: Control and Signaling Voltage 24 VDC				
108	Note 6: LVS Jirkov is alternative location to LVS Vrskman. Only one LVS of those two stations shall be constructed, either Jirkov or Vrskman				
109	Note 7: The type of wiring diagram shall be "TPCAA121D1H1-E460 TPA00R200-012-000"				
110					
111					
112					
113					
114					
115					
116					
117					

BALL VALVE - DN 500

1	GENERAL INFORMATION				
2	LOCATION	LVS HRUSOVANY	5	QUANTITY	2
3	EQUIPMENT	BALL VALVE	6	TECHNICAL SPECIFICATION	C4G-HPPL-ILF-GENER-STR-SPC-824
4	TAG No.	MOV-7.3, MOV-7.4	7	P&ID-No.	C4G-HPPL-ILF-TU51S-STR-DIA-110
8	OPERATION AND DESIGN DATA				
9	AMBIENT CONDITIONS	C4G-HPPL-ILF-GENER-GEN-SPC-901	16	MAX. OPERATING PRESSURE	85 barg
10	MEDIUM	NATURAL GAS	17	OPERATING TEMPERATURE	+5 to +25 °C
11	GAS COMPOSITION	C4G-HPPL-ILF-GENER-GEN-DAT-820	18	DESIGN PRESSURE	100 barg
12	PIPING CLASS	CS100-0	19	DESIGN TEMPERATURE	-20 to +50 °C
13	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	20	TEST PRESSURE	150 barg
14	FLANGE STANDARD / RATING	N/A	21	SAFETY FACTOR (TO YIELD POINT)	2.15
15	INSTALLATION	ABOVEGROUND	22	SAFETY FACTOR ON WELD ENDS (TO YIELD POINT)	1.68
23	VALVE DATA				
24	VALVE BODY / BALL DESIGN	FULLY WELDED BODY	36	SUPPORT LEGS	YES
25	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	37	LIFTING LUGS	YES
26	NOMINAL PIPE SIZE / OD / THICKNESS	DN 500 / 508 mm / 12.5 mm	38	FLOW DIRECTION	BIDIRECTIONAL
27	PIPELINE CONNECTION TYPE	WELD / WELD	39	LEAK RATE	ACC. TO EN 12266-1, -2; RATE A
28	MAIN SEALS	METAL	40	MAX. VALVE LIFT	*
29	SECONDARY SEALS	SOFT	41	STEM DIAMETER / TYPE	* / ANTI-BLOW-OUT
30	SEATS RINGS	DOUBLE PISTON EFFECT	42	LOCK POSITION	YES
31	CAVITY PRESSURE RELIEF VALVE	N/A	43	ADJUSTABLE LIMIT STOP	*
32	DOUBLE BLOCK & BLEED	YES	44	ANTI STATIC DESIGN	YES
33	VENT	YES	45	FIRE SAFE DESIGN	YES
34	DRAIN	YES	46	SEALANT LINE INJECTION MEDIA	4 INDPEDENT GREASE FITTINGS
35	INSULATION	NO	47		
48	ACTUATOR AND ACCESSORIES				
49	ACTUATOR TYPE	ELECTRO MOTOR (Note 2) (Note 6)	61	STROKING TIME TO OPEN (Min./Max.)	40 s/180 s
50	MANUFACTURER/ MODEL	AUMATIC SAEx	62	STROKING TIME TO CLOSE (Min./Max.)	60 s /180 s
51	GEAR BOX WITH HANDWHEEL	N/A	63	LIMIT SWITCH	YES
52	DESIGN TORQUE FOR ACTUATOR	*	64	POSITIONER MANUFACT / MODEL	*
53	ACTUATOR ATTACHMENT	ACC. TO EN ISO 5211	65	STEM	*
54	FAIL SAFE POSITION	N/A	66	STEM EXTENSION FOR UNDERGROUND	VALVE CL TO ACTUATOR FLANGE
55	POWER SUPPLY	400V / 50 Hz / 3 Ph	67	INSTALLATION	VALVE CL TO GROUND LEVEL
56	IP-CODE	IP 65 (IEC 60529)	68	BY-PASS AND AIR-BLEED VALVE	N/A
57	INSULATING CLASS	I	69	OIL AND GAS FILTERS	N/A
58	HAZARDOUS AREA	ZONE 1	70	CONTROL UNIT	C4G-HPPL-ILF-GENER-STR-SPC-824
59	EXPLOSION PROTECTION	II 2G IIB T3	71	ACTUATOR LOCKING	SELF LOCKING
60	MINIMUM SUPPLY PRESSURE	N/A	72	MECANICAL POSITION INDICATOR	YES - OPEN/CLOSE
73	DIMENSIONS, WEIGHT, MECHANICAL AND ELECTRICAL INTERFACES				
74	FITTING LENGTH	*	78	WEIGHT (VALVE)	*
75	FITTING HEIGHT	*	79	WEIGHT (VALVE + ACTUATOR)	*
76	WALL THICKNESS	*	80	CABLE CONNECTION TYPE	Exd Cable Gland
77			81	CABLE CONNECTION SIZE	*
82	MATERIALS, TESTING AND DOCUMENTATION				
83	MATERIAL OF PIPE END	L360NE	92	STANDARD TEST	ACC TO CSN EN 14141 / API 6D
84	VALVE MATERIAL	ACC. TO ČSN EN 1594/API 6D	93	LEAKAGE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
85	BALL MATERIAL	C4G-HPPL-ILF-GENER-STR-SPC-824	94	PRESSURE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
86	PUP PIECES MATERIAL	*	95	TIGHTNESS TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
87	MATERIAL STEM	*	96	FIRE SAFE TEST	ACC. TO API 607 / ISO 10497
88	MATERIAL BOLTS / NUTS	ACC. TO ČSN EN ISO 898	97	ATEX CERTIFICATION	ACC. TO CSN EN 60079-10
89	MATERIAL SEAT / SEAL	A350 LF2 / HNBR (Therban) *	98	SAFETY INTEGRITY LEVEL	N/A
90	ANTI - CORROSION PROTECTION	C4G-HPPL-ILF-GENER-STR-SPC-824	99	FINAL ACCEPTANCE TEST	ČSN EN 10204 / 3.2
91	DOCUMENTATION	C4G-HPPL-ILF-GENER-STR-SPC-824	100	CE-CONFORMITY	ACC. TO PED 2014/68/EU
101	NOTES				
102	* To be filled/confirmed by Supplier				
103	Note 1: This data sheet shall be read with the Specification C4G-HPPL-ILF-GENER-STR-SPC-824				
104	Note 2: Motor Operated Valve (MOV) with Local and Remote Control and Monitoring Functionality				
105	Note 3: CL - Center Line				
106	Note 4: N/A - Not Applicable				
107	Note 5: Control and Signaling Voltage 24 VDC				
108	Note 6: The type of wiring diagram shall be "TPCAA121D1H1-E460 TPA00R200-012-000"				
109					
110					
111					
112					
113					
114					
115					
116					
117					

BALL VALVE - DN 500					
1	GENERAL INFORMATION				
2	LOCATION	LVS SYROVICE	5	QUANTITY	2
3	EQUIPMENT	BALL VALVE	6	TECHNICAL SPECIFICATION	C4G-HPPL-ILF-GENER-STR-SPC-824
4	TAG No.	MOV-7.3, MOV-7.4	7	P&ID-No.	C4G-HPPL-ILF-TU52S-STR-DIA-110
8	OPERATION AND DESIGN DATA				
9	AMBIENT CONDITIONS	C4G-HPPL-ILF-GENER-GEN-SPC-901	16	MAX. OPERATING PRESSURE	85 barg
10	MEDIUM	NATURAL GAS	17	OPERATING TEMPERATURE	+5 to +25 °C
11	GAS COMPOSITION	C4G-HPPL-ILF-GENER-GEN-DAT-820	18	DESIGN PRESSURE	100 barg
12	PIPING CLASS	CS100-0	19	DESIGN TEMPERATURE	-20 to +50 °C
13	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	20	TEST PRESSURE	150 barg
14	FLANGE STANDARD / RATING	N/A	21	SAFETY FACTOR (TO YIELD POINT)	2.15
15	INSTALLATION	ABOVEGROUND	22	SAFETY FACTOR ON WELD ENDS (TO YIELD POINT)	1.68
23	VALVE DATA				
24	VALVE BODY / BALL DESIGN	FULLY WELDED BODY	36	SUPPORT LEGS	YES
25	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	37	LIFTING LUGS	YES
26	NOMINAL PIPE SIZE / OD / THICKNESS	DN 500 / 508 mm / 12.5 mm	38	FLOW DIRECTION	BIDIRECTIONAL
27	PIPELINE CONNECTION TYPE	WELD / WELD	39	LEAK RATE	ACC. TO EN 12266-1, -2; RATE A
28	MAIN SEALS	METAL	40	MAX. VALVE LIFT	*
29	SECONDARY SEALS	SOFT	41	STEM DIAMETER / TYPE	* / ANTI-BLOW-OUT
30	SEATS RINGS	DOUBLE PISTON EFFECT	42	LOCK POSITION	YES
31	CAVITY PRESSURE RELIEF VALVE	N/A	43	ADJUSTABLE LIMIT STOP	*
32	DOUBLE BLOCK & BLEED	YES	44	ANTI STATIC DESIGN	YES
33	VENT	YES	45	FIRE SAFE DESIGN	YES
34	DRAIN	YES	46	SEALANT LINE INJECTION MEDIA	4 INDPEDENT GREASE FITTINGS
35	INSULATION	NO	47		
48	ACTUATOR AND ACCESSORIES				
49	ACTUATOR TYPE	ELECTRO MOTOR (Note 2) (Note 6)	61	STROKING TIME TO OPEN (Min./Max.)	40 s/180 s
50	MANUFACTURER/ MODEL	AUMATIC SAEx	62	STROKING TIME TO CLOSE (Min./Max.)	60 s /180 s
51	GEAR BOX WITH HANDWHEEL	N/A	63	LIMIT SWITCH	YES
52	DESIGN TORQUE FOR ACTUATOR	*	64	POSITIONER MANUFACT / MODEL	*
53	ACTUATOR ATTACHMENT	ACC. TO EN ISO 5211	65	STEM	*
54	FAIL SAFE POSITION	N/A	66	STEM EXTENSION FOR UNDERGROUND	VALVE CL TO ACTUATOR FLANGE
55	POWER SUPPLY	400V / 50 Hz / 3 Ph	67	INSTALLATION	VALVE CL TO GROUND LEVEL
56	IP-CODE	IP 65 (IEC 60529)	68	BY-PASS AND AIR-BLEED VALVE	N/A
57	INSULATING CLASS	I	69	OIL AND GAS FILTERS	N/A
58	HAZARDOUS AREA	ZONE 1	70	CONTROL UNIT	C4G-HPPL-ILF-GENER-STR-SPC-824
59	EXPLOSION PROTECTION	II 2G IIB T3	71	ACTUATOR LOCKING	SELF LOCKING
60	MINIMUM SUPPLY PRESSURE	N/A	72	MECHANICAL POSITION INDICATOR	YES - OPEN/CLOSE
73	DIMENSIONS, WEIGHT, MECHANICAL AND ELECTRICAL INTERFACES				
74	FITTING LENGTH	*	78	WEIGHT (VALVE)	*
75	FITTING HEIGHT	*	79	WEIGHT (VALVE + ACTUATOR)	*
76	WALL THICKNESS	*	80	CABLE CONNECTION TYPE	Exd Cable Gland
77			81	CABLE CONNECTION SIZE	*
82	MATERIALS, TESTING AND DOCUMENTATION				
83	MATERIAL OF PIPE END	L360NE	92	STANDARD TEST	ACC TO CSN EN 14141 / API 6D
84	VALVE MATERIAL	ACC. TO ČSN EN 1594/API 6D	93	LEAKAGE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
85	BALL MATERIAL	C4G-HPPL-ILF-GENER-STR-SPC-824	94	PRESSURE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
86	PUP PIECES MATERIAL	*	95	TIGHTNESS TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
87	MATERIAL STEM	*	96	FIRE SAFE TEST	ACC. TO API 607 / ISO 10497
88	MATERIAL BOLTS / NUTS	ACC. TO ČSN EN ISO 898	97	ATEX CERTIFICATION	ACC. TO CSN EN 60079-10
89	MATERIAL SEAT / SEAL	A350 LF2 / HNBR (Therban) *	98	SAFETY INTEGRITY LEVEL	N/A
90	ANTI - CORROSION PROTECTION	C4G-HPPL-ILF-GENER-STR-SPC-824	99	FINAL ACCEPTANCE TEST	ČSN EN 10204 / 3.2
91	DOCUMENTATION	C4G-HPPL-ILF-GENER-STR-SPC-824	100	CE-CONFORMITY	ACC. TO PED 2014/68/EU
101	NOTES				
102	* To be filled/confirmed by Supplier				
103	Note 1: This data sheet shall be read with the Specification C4G-HPPL-ILF-GENER-STR-SPC-824				
104	Note 2: Motor Operated Valve (MOV) with Local and Remote Control and Monitoring Functionality				
105	Note 3: CL - Center Line				
106	Note 4: N/A - Not Applicable				
107	Note 5: Control and Signaling Voltage 24 VDC				
108	Note 6: The type of wiring diagram shall be "TPCAA121D1H1-E460 TPA00R200-012-000"				
109					
110					
111					
112					
113					
114					
115					
116					
117					

BALL VALVE - DN 1200					
1	GENERAL INFORMATION				
2	LOCATION	LVS MALMERICE	5	QUANTITY	1
3	EQUIPMENT	BALL VALVE	6	TECHNICAL SPECIFICATION	C4G-HPPL-ILF-GENER-STR-SPC-824
4	TAG No.	GHV-2.3	7	P&ID-No.	C4G-HPPL-ILF-TU53S-STR-DIA-110
8	OPERATION AND DESIGN DATA				
9	AMBIENT CONDITIONS	C4G-HPPL-ILF-GENER-GEN-SPC-901	16	MAX. OPERATING PRESSURE	85 barg
10	MEDIUM	NATURAL GAS	17	OPERATING TEMPERATURE	+5 to +25 °C
11	GAS COMPOSITION	C4G-HPPL-ILF-GENER-GEN-DAT-820	18	DESIGN PRESSURE	100 barg
12	PIPING CLASS	CS100-0	19	DESIGN TEMPERATURE	-20 to +50 °C
13	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	20	TEST PRESSURE	150 barg
14	FLANGE STANDARD / RATING	N/A	21	SAFETY FACTOR (TO YIELD POINT)	2.15
15	INSTALLATION	UNDERGROUND	22	SAFETY FACTOR ON WELD ENDS (TO YIELD POINT)	1.68
23	VALVE DATA				
24	VALVE BODY / BALL DESIGN	FULLY WELDED BODY - FULL BORE	36	SUPPORT LEGS	YES
25	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	37	LIFTING LUGS	YES
26	NOMINAL PIPE SIZE / OD / THICKNESS	DN 1200 / 1219 mm / 22.2 mm	38	FLOW DIRECTION	BIDIRECTIONAL
27	PIPELINE CONNECTION TYPE	WELD / WELD	39	LEAK RATE	ACC. TO EN 12266-1, -2; RATE A
28	MAIN SEALS	METAL	40	MAX. VALVE LIFT	*
29	SECONDARY SEALS	SOFT	41	STEM DIAMETER / TYPE	* / ANTI-BLOW-OUT
30	SEATS RINGS	DOUBLE PISTON EFFECT	42	LOCK POSITION	NO
31	CAVITY PRESSURE RELIEF VALVE	N/A	43	ADJUSTABLE LIMIT STOP	*
32	DOUBLE BLOCK & BLEED	YES	44	ANTI STATIC DESIGN	YES
33	VENT	YES	45	FIRE SAFE DESIGN	YES
34	DRAIN	YES	46	SEALANT LINE INJECTION MEDIA	4 INDPEDENT GREASE FITTINGS
35	INSULATION	NO	47		
48	ACTUATOR AND ACCESSORIES				
49	ACTUATOR TYPE	GAS HYDRAULIC WITH LBC (Note 2) (Note 6)	61	STROKING TIME TO OPEN (Min./Max.)	60 s/180 s
50	MANUFACTURER/ MODEL	*	62	STROKING TIME TO CLOSE (Min./Max.)	60 s /180 s
51	GEAR BOX WITH HANDWHEEL	N/A	63	LIMIT SWITCH	YES
52	DESIGN TORQUE FOR ACTUATOR	*	64	POSITIONER MANUFACT / MODEL	*
53	ACTUATOR ATTACHMENT	ACC. TO EN ISO 5211	65	STEM	*
54	FAIL SAFE POSITION	N/A	66	STEM EXTENSION FOR UNDERGROUND INSTALLATION	VALVE CL TO ACTUATOR FLANGE 2420 mm * VALVE CL TO GROUND LEVEL 1670 mm
55	POWER SUPPLY	N/A	67		
56	IP-CODE	IP 65 (IEC 60529)	68	BY-PASS AND AIR-BLEED VALVE	N/A
57	INSULATING CLASS	I	69	OIL AND GAS FILTERS	YES
58	HAZARDOUS AREA	ZONE 1	70	CONTROL UNIT	C4G-HPPL-ILF-GENER-STR-SPC-824
59	EXPLOSION PROTECTION	II 2G IIB T3	71	ACTUATOR LOCKING	SELF LOCKING
60	MINIMUM SUPPLY PRESSURE	38.0 barg	72	MECHANICAL POSITION INDICATOR	YES - OPEN/CLOSE
73	DIMENSIONS, WEIGHT, MECHANICAL AND ELECTRICAL INTERFACES				
74	FITTING LENGTH	*	78	WEIGHT (VALVE)	*
75	FITTING HEIGHT	*	79	WEIGHT (VALVE + ACTUATOR)	*
76	WALL THICKNESS	*	80	CABLE CONNECTION TYPE	N/A
77			81	CABLE CONNECTION SIZE	*
82	MATERIALS, TESTING AND DOCUMENTATION				
83	MATERIAL OF PIPE END	L485ME	92	STANDARD TEST	ACC TO CSN EN 14141 / API 6D
84	VALVE MATERIAL	ACC. TO ČSN EN 1594/API 6D	93	LEAKAGE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
85	BALL MATERIAL	C4G-HPPL-ILF-GENER-STR-SPC-824	94	PRESSURE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
86	PUP PIECES MATERIAL	*	95	TIGHTNESS TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
87	MATERIAL STEM	*	96	FIRE SAFE TEST	ACC. TO API 607 / ISO 10497
88	MATERIAL BOLTS / NUTS	ACC. TO ČSN EN ISO 898	97	ATEX CERTIFICATION	ACC. TO CSN EN 60079-10
89	MATERIAL SEAT / SEAL	A350 LF2 / HNBR (Therban) *	98	SAFETY INTEGRITY LEVEL	N/A
90	ANTI - CORROSION PROTECTION	C4G-HPPL-ILF-GENER-STR-SPC-824	99	FINAL ACCEPTANCE TEST	ČSN EN 10204 / 3.2
91	DOCUMENTATION	C4G-HPPL-ILF-GENER-STR-SPC-824	100	CE-CONFORMITY	ACC. TO PED 2014/68/EU
101	NOTES				
102	* To be filled/confirmed by Supplier				
103	Note 1: This data sheet shall be read with the Specification C4G-HPPL-ILF-GENER-STR-SPC-824				
104	Note 2: Gas Hydraulic Valve (GHV) with Local and Remote Control and Monitoring Functionality and Line Break Control (LBC)				
105	Note 3: CL - Center Line				
106	Note 4: N/A - Not Applicable				
107	Note 5: Control and Signaling Voltage 24 VDC				
108	Note 6: LBC - Line Break Control shall be mechanical type. Pre-set pressure drop shall be 5 bar/min, and shall be ajustable				
109					
110					
111					
112					
113					
114					
115					
116					
117					

BALL VALVE - DN 500

1	GENERAL INFORMATION				
2	LOCATION	LVS MALMERICE	5	QUANTITY	4
3	EQUIPMENT	BALL VALVE	6	TECHNICAL SPECIFICATION	C4G-HPPL-ILF-GENER-STR-SPC-824
4	TAG No.	MOV-7.5, MOV-7.6, MOV-7.7, MOV-7.8	7	P&ID-No.	C4G-HPPL-ILF-TU53S-STR-DIA-110
8	OPERATION AND DESIGN DATA				
9	AMBIENT CONDITIONS	C4G-HPPL-ILF-GENER-GEN-SPC-901	16	MAX. OPERATING PRESSURE	85 barg
10	MEDIUM	NATURAL GAS	17	OPERATING TEMPERATURE	+5 to +25 °C
11	GAS COMPOSITION	C4G-HPPL-ILF-GENER-GEN-DAT-820	18	DESIGN PRESSURE	100 barg
12	PIPING CLASS	CS100-0	19	DESIGN TEMPERATURE	-20 to +50 °C
13	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	20	TEST PRESSURE	150 barg
14	FLANGE STANDARD / RATING	N/A	21	SAFETY FACTOR (TO YIELD POINT)	2.15
15	INSTALLATION	ABOVEGROUND	22	SAFETY FACTOR ON WELD ENDS (TO YIELD POINT)	1.68
23	VALVE DATA				
24	VALVE BODY / BALL DESIGN	FULLY WELDED BODY	36	SUPPORT LEGS	YES
25	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	37	LIFTING LUGS	YES
26	NOMINAL PIPE SIZE / OD / THICKNESS	DN 500 / 508 mm / 12.5 mm	38	FLOW DIRECTION	BIDIRECTIONAL
27	PIPELINE CONNECTION TYPE	WELD / WELD	39	LEAK RATE	ACC. TO EN 12266-1, -2; RATE A
28	MAIN SEALS	METAL	40	MAX. VALVE LIFT	*
29	SECONDARY SEALS	SOFT	41	STEM DIAMETER / TYPE	* / ANTI-BLOW-OUT
30	SEATS RINGS	DOUBLE PISTON EFFECT	42	LOCK POSITION	YES
31	CAVITY PRESSURE RELIEF VALVE	N/A	43	ADJUSTABLE LIMIT STOP	*
32	DOUBLE BLOCK & BLEED	YES	44	ANTI STATIC DESIGN	YES
33	VENT	YES	45	FIRE SAFE DESIGN	YES
34	DRAIN	YES	46	SEALANT LINE INJECTION MEDIA	4 INDPEDENT GREASE FITTINGS
35	INSULATION	NO	47		
48	ACTUATOR AND ACCESSORIES				
49	ACTUATOR TYPE	ELECTRO MOTOR (Note 2) (Note 6)	61	STROKING TIME TO OPEN (Min./Max.)	40 s/180 s
50	MANUFACTURER/ MODEL	AUMATIC SAEx	62	STROKING TIME TO CLOSE (Min./Max.)	60 s /180 s
51	GEAR BOX WITH HANDWHEEL	N/A	63	LIMIT SWITCH	YES
52	DESIGN TORQUE FOR ACTUATOR	*	64	POSITIONER MANUFACT / MODEL	*
53	ACTUATOR ATTACHMENT	ACC. TO EN ISO 5211	65	STEM	*
54	FAIL SAFE POSITION	N/A	66	STEM EXTENSION FOR UNDERGROUND	VALVE CL TO ACTUATOR FLANGE
55	POWER SUPPLY	400V / 50 Hz / 3 Ph	67	INSTALLATION	VALVE CL TO GROUND LEVEL
56	IP-CODE	IP 65 (IEC 60529)	68	BY-PASS AND AIR-BLEED VALVE	N/A
57	INSULATING CLASS	I	69	OIL AND GAS FILTERS	N/A
58	HAZARDOUS AREA	ZONE 1	70	CONTROL UNIT	C4G-HPPL-ILF-GENER-STR-SPC-824
59	EXPLOSION PROTECTION	II 2G IIB T3	71	ACTUATOR LOCKING	SELF LOCKING
60	MINIMUM SUPPLY PRESSURE	N/A	72	MECANICAL POSITION INDICATOR	YES - OPEN/CLOSE
73	DIMENSIONS, WEIGHT, MECHANICAL AND ELECTRICAL INTERFACES				
74	FITTING LENGTH	*	78	WEIGHT (VALVE)	*
75	FITTING HEIGHT	*	79	WEIGHT (VALVE + ACTUATOR)	*
76	WALL THICKNESS	*	80	CABLE CONNECTION TYPE	Exd Cable Gland
77			81	CABLE CONNECTION SIZE	*
82	MATERIALS, TESTING AND DOCUMENTATION				
83	MATERIAL OF PIPE END	L360NE	92	STANDARD TEST	ACC TO CSN EN 14141 / API 6D
84	VALVE MATERIAL	ACC. TO ČSN EN 1594/API 6D	93	LEAKAGE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
85	BALL MATERIAL	C4G-HPPL-ILF-GENER-STR-SPC-824	94	PRESSURE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
86	PUP PIECES MATERIAL	*	95	TIGHTNESS TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
87	MATERIAL STEM	*	96	FIRE SAFE TEST	ACC. TO API 607 / ISO 10497
88	MATERIAL BOLTS / NUTS	ACC. TO ČSN EN ISO 898	97	ATEX CERTIFICATION	ACC. TO CSN EN 60079-10
89	MATERIAL SEAT / SEAL	A350 LF2 / HNBR (Therban) *	98	SAFETY INTEGRITY LEVEL	N/A
90	ANTI - CORROSION PROTECTION	C4G-HPPL-ILF-GENER-STR-SPC-824	99	FINAL ACCEPTANCE TEST	ČSN EN 10204 / 3.2
91	DOCUMENTATION	C4G-HPPL-ILF-GENER-STR-SPC-824	100	CE-CONFORMITY	ACC. TO PED 2014/68/EU
101	NOTES				
102	* To be filled/confirmed by Supplier				
103	Note 1: This data sheet shall be read with the Specification C4G-HPPL-ILF-GENER-STR-SPC-824				
104	Note 2: Motor Operated Valve (MOV) with Local and Remote Control and Monitoring Functionality				
105	Note 3: CL - Center Line				
106	Note 4: N/A - Not Applicable				
107	Note 5: Control and Signaling Voltage 24 VDC				
108	Note 6: The type of wiring diagram shall be "TPCAA121D1H1-E460 TPA00R200-012-000"				
109					
110					
111					
112					
113					
114					
115					
116					
117					

BALL VALVE - DN 300					
1	GENERAL INFORMATION				
2	LOCATION	LVS MALMERICE	5	QUANTITY	2
3	EQUIPMENT	BALL VALVE	6	TECHNICAL SPECIFICATION	C4G-HPPL-ILF-GENER-STR-SPC-824
4	TAG No.	MOV-8.10, MOV-8.12	7	P&ID-No.	C4G-HPPL-ILF-TU53S-STR-DIA-110
8	OPERATION AND DESIGN DATA				
9	AMBIENT CONDITIONS	C4G-HPPL-ILF-GENER-GEN-SPC-901	16	MAX. OPERATING PRESSURE	85 barg
10	MEDIUM	NATURAL GAS	17	OPERATING TEMPERATURE	+5 to +25 °C
11	GAS COMPOSITION	C4G-HPPL-ILF-GENER-GEN-DAT-820	18	DESIGN PRESSURE	100 barg
12	PIPING CLASS	CS100-0	19	DESIGN TEMPERATURE	-20 to +50 °C
13	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	20	TEST PRESSURE	150 barg
14	FLANGE STANDARD / RATING	N/A	21	SAFETY FACTOR (TO YIELD POINT)	2.15
15	INSTALLATION	ABOVEGROUND	22	SAFETY FACTOR ON WELD ENDS (TO YIELD POINT)	1.68
23	VALVE DATA				
24	VALVE BODY / BALL DESIGN	FULLY WELDED BODY	36	SUPPORT LEGS	YES
25	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	37	LIFTING LUGS	YES
26	NOMINAL PIPE SIZE / OD / THICKNESS	DN 300 / 323.9 mm / 8.8 mm	38	FLOW DIRECTION	BIDIRECTIONAL
27	PIPELINE CONNECTION TYPE	WELD / WELD	39	LEAK RATE	ACC. TO EN 12266-1, -2; RATE A
28	MAIN SEALS	METAL	40	MAX. VALVE LIFT	*
29	SECONDARY SEALS	SOFT	41	STEM DIAMETER / TYPE	* / ANTI-BLOW-OUT
30	SEATS RINGS	DOUBLE PISTON EFFECT	42	LOCK POSITION	YES
31	CAVITY PRESSURE RELIEF VALVE	N/A	43	ADJUSTABLE LIMIT STOP	*
32	DOUBLE BLOCK & BLEED	YES	44	ANTI STATIC DESIGN	YES
33	VENT	YES	45	FIRE SAFE DESIGN	YES
34	DRAIN	YES	46	SEALANT LINE INJECTION MEDIA	4 INDPEDENT GREASE FITTINGS
35	INSULATION	NO	47		
48	ACTUATOR AND ACCESSORIES				
49	ACTUATOR TYPE	ELECTRO MOTOR (Note 2) (Note 6)	61	STROKING TIME TO OPEN (Min./Max.)	40 s/180 s
50	MANUFACTURER/ MODEL	AUMATIC SAEx	62	STROKING TIME TO CLOSE (Min./Max.)	60 s /180 s
51	GEAR BOX WITH HANDWHEEL	N/A	63	LIMIT SWITCH	YES
52	DESIGN TORQUE FOR ACTUATOR	*	64	POSITIONER MANUFACT / MODEL	*
53	ACTUATOR ATTACHMENT	ACC. TO EN ISO 5211	65	STEM	*
54	FAIL SAFE POSITION	N/A	66	STEM EXTENSION FOR UNDERGROUND	VALVE CL TO ACTUATOR FLANGE
55	POWER SUPPLY	400V / 50 Hz / 3 Ph	67	INSTALLATION	VALVE CL TO GROUND LEVEL
56	IP-CODE	IP 65 (IEC 60529)	68	BY-PASS AND AIR-BLEED VALVE	N/A
57	INSULATING CLASS	I	69	OIL AND GAS FILTERS	N/A
58	HAZARDOUS AREA	ZONE 1	70	CONTROL UNIT	C4G-HPPL-ILF-GENER-STR-SPC-824
59	EXPLOSION PROTECTION	II 2G IIB T3	71	ACTUATOR LOCKING	SELF LOCKING
60	MINIMUM SUPPLY PRESSURE	N/A	72	MECHANICAL POSITION INDICATOR	YES - OPEN/CLOSE
73	DIMENSIONS, WEIGHT, MECHANICAL AND ELECTRICAL INTERFACES				
74	FITTING LENGTH	*	78	WEIGHT (VALVE)	*
75	FITTING HEIGHT	*	79	WEIGHT (VALVE + ACTUATOR)	*
76	WALL THICKNESS	*	80	CABLE CONNECTION TYPE	Exd Cable Gland
77			81	CABLE CONNECTION SIZE	*
82	MATERIALS, TESTING AND DOCUMENTATION				
83	MATERIAL OF PIPE END	L360NE	92	STANDARD TEST	ACC TO CSN EN 14141 / API 6D
84	VALVE MATERIAL	ACC. TO ČSN EN 1594/API 6D	93	LEAKAGE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
85	BALL MATERIAL	C4G-HPPL-ILF-GENER-STR-SPC-824	94	PRESSURE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
86	PUP PIECES MATERIAL	*	95	TIGHTNESS TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
87	MATERIAL STEM	*	96	FIRE SAFE TEST	ACC. TO API 607 / ISO 10497
88	MATERIAL BOLTS / NUTS	ACC. TO ČSN EN ISO 898	97	ATEX CERTIFICATION	ACC. TO CSN EN 60079-10
89	MATERIAL SEAT / SEAL	A350 LF2 / HNBR (Therban) *	98	SAFETY INTEGRITY LEVEL	N/A
90	ANTI - CORROSION PROTECTION	C4G-HPPL-ILF-GENER-STR-SPC-824	99	FINAL ACCEPTANCE TEST	ČSN EN 10204 / 3.2
91	DOCUMENTATION	C4G-HPPL-ILF-GENER-STR-SPC-824	100	CE-CONFORMITY	ACC. TO PED 2014/68/EU
101	NOTES				
102	* To be filled/confirmed by Supplier				
103	Note 1: This data sheet shall be read with the Specification C4G-HPPL-ILF-GENER-STR-SPC-824				
104	Note 2: Motor Operated Valve (MOV) with Local Control and Monitoring as well as Remote Open/Closed Monitoring Functionality				
105	Note 3: CL - Center Line				
106	Note 4: N/A - Not Applicable				
107	Note 5: Control and Signaling Voltage 24 VDC				
108	Note 6: The type of wiring diagram shall be "TPCAA121D1H1-E460 TPA00R200-012-000"				
109					
110					
111					
112					
113					
114					
115					
116					
117					

BALL VALVE - DN 300

1	GENERAL INFORMATION				
2	LOCATION	LVS MALMERICE	5	QUANTITY	2
3	EQUIPMENT	BALL VALVE	6	TECHNICAL SPECIFICATION	C4G-HPPL-ILF-GENER-STR-SPC-824
4	TAG No.	MOV-8.11, MOV-8.13	7	P&ID-No.	C4G-HPPL-ILF-TU53S-STR-DIA-110
8	OPERATION AND DESIGN DATA				
9	AMBIENT CONDITIONS	C4G-HPPL-ILF-GENER-GEN-SPC-901	16	MAX. OPERATING PRESSURE	85 barg
10	MEDIUM	NATURAL GAS	17	OPERATING TEMPERATURE	+5 to +25 °C
11	GAS COMPOSITION	C4G-HPPL-ILF-GENER-GEN-DAT-820	18	DESIGN PRESSURE	100 barg
12	PIPING CLASS	CS100-0	19	DESIGN TEMPERATURE	-20 to +50 °C
13	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	20	TEST PRESSURE	150 barg
14	FLANGE STANDARD / RATING	N/A	21	SAFETY FACTOR (TO YIELD POINT)	2.15
15	INSTALLATION	ABOVEGROUND	22	SAFETY FACTOR ON WELD ENDS (TO YIELD POINT)	1.68
23	VALVE DATA				
24	VALVE BODY / BALL DESIGN	FULLY WELDED BODY	36	SUPPORT LEGS	YES
25	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	37	LIFTING LUGS	YES
26	NOMINAL PIPE SIZE / OD / THICKNESS	DN 300 / 323.9 mm / 8.8 mm	38	FLOW DIRECTION	BIDIRECTIONAL
27	PIPELINE CONNECTION TYPE	WELD / WELD	39	LEAK RATE	ACC. TO EN 12266-1, -2; RATE A
28	MAIN SEALS	METAL	40	MAX. VALVE LIFT	*
29	SECONDARY SEALS	SOFT	41	STEM DIAMETER / TYPE	* / ANTI-BLOW-OUT
30	SEATS RINGS	DOUBLE PISTON EFFECT	42	LOCK POSITION	YES
31	CAVITY PRESSURE RELIEF VALVE	N/A	43	ADJUSTABLE LIMIT STOP	*
32	DOUBLE BLOCK & BLEED	YES	44	ANTI STATIC DESIGN	YES
33	VENT	YES	45	FIRE SAFE DESIGN	YES
34	DRAIN	YES	46	SEALANT LINE INJECTION MEDIA	4 INDPEDENT GREASE FITTINGS
35	INSULATION	NO	47		
48	ACTUATOR AND ACCESSORIES				
49	ACTUATOR TYPE	ELECTRO MOTOR (Note 2) (Note 6)	61	STROKING TIME TO OPEN (Min./Max.)	40 s/180 s
50	MANUFACTURER/ MODEL	AUMATIC SAEx	62	STROKING TIME TO CLOSE (Min./Max.)	60 s /180 s
51	GEAR BOX WITH HANDWHEEL	N/A	63	LIMIT SWITCH	YES
52	DESIGN TORQUE FOR ACTUATOR	*	64	POSITIONER MANUFACT / MODEL	*
53	ACTUATOR ATTACHMENT	ACC. TO EN ISO 5211	65	STEM	*
54	FAIL SAFE POSITION	N/A	66	STEM EXTENSION FOR UNDERGROUND	VALVE CL TO ACTUATOR FLANGE
55	POWER SUPPLY	400V / 50 Hz / 3 Ph	67	INSTALLATION	VALVE CL TO GROUND LEVEL
56	IP-CODE	IP 65 (IEC 60529)	68	BY-PASS AND AIR-BLEED VALVE	N/A
57	INSULATING CLASS	I	69	OIL AND GAS FILTERS	N/A
58	HAZARDOUS AREA	ZONE 1	70	CONTROL UNIT	C4G-HPPL-ILF-GENER-STR-SPC-824
59	EXPLOSION PROTECTION	II 2G IIB T3	71	ACTUATOR LOCKING	SELF LOCKING
60	MINIMUM SUPPLY PRESSURE	N/A	72	MECANICAL POSITION INDICATOR	YES - OPEN/CLOSE
73	DIMENSIONS, WEIGHT, MECHANICAL AND ELECTRICAL INTERFACES				
74	FITTING LENGTH	*	78	WEIGHT (VALVE)	*
75	FITTING HEIGHT	*	79	WEIGHT (VALVE + ACTUATOR)	*
76	WALL THICKNESS	*	80	CABLE CONNECTION TYPE	Exd Cable Gland
77			81	CABLE CONNECTION SIZE	*
82	MATERIALS, TESTING AND DOCUMENTATION				
83	MATERIAL OF PIPE END	L360NE	92	STANDARD TEST	ACC TO CSN EN 14141 / API 6D
84	VALVE MATERIAL	ACC. TO ČSN EN 1594/API 6D	93	LEAKAGE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
85	BALL MATERIAL	C4G-HPPL-ILF-GENER-STR-SPC-824	94	PRESSURE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
86	PUP PIECES MATERIAL	*	95	TIGHTNESS TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
87	MATERIAL STEM	*	96	FIRE SAFE TEST	ACC. TO API 607 / ISO 10497
88	MATERIAL BOLTS / NUTS	ACC. TO ČSN EN ISO 898	97	ATEX CERTIFICATION	ACC. TO CSN EN 60079-10
89	MATERIAL SEAT / SEAL	A350 LF2 / HNBR (Therban) *	98	SAFETY INTEGRITY LEVEL	N/A
90	ANTI - CORROSION PROTECTION	C4G-HPPL-ILF-GENER-STR-SPC-824	99	FINAL ACCEPTANCE TEST	ČSN EN 10204 / 3.2
91	DOCUMENTATION	C4G-HPPL-ILF-GENER-STR-SPC-824	100	CE-CONFORMITY	ACC. TO PED 2014/68/EU
101	NOTES				
102	* To be filled/confirmed by Supplier				
103	Note 1: This data sheet shall be read with the Specification C4G-HPPL-ILF-GENER-STR-SPC-824				
104	Note 2: Motor Operated Valve (MOV) with Local Control and Monitoring				
105	Note 3: CL - Center Line				
106	Note 4: N/A - Not Applicable				
107	Note 5: Control and Signaling Voltage 24 VDC				
108	Note 6: The type of wiring diagram shall be "TPCAA121D1H1-E460 TPA00R200-012-000"				
109					
110					
111					
112					
113					
114					
115					
116					
117					

BALL VALVE - DN 300

1	GENERAL INFORMATION				
2	LOCATION	LVS MALMERICE	5	QUANTITY	1
3	EQUIPMENT	BALL VALVE	6	TECHNICAL SPECIFICATION	C4G-HPPL-ILF-GENER-STR-SPC-824
4	TAG No.	8.14	7	P&ID-No.	C4G-HPPL-ILF-TU53S-STR-DIA-110
8	OPERATION AND DESIGN DATA				
9	AMBIENT CONDITIONS	C4G-HPPL-ILF-GENER-GEN-SPC-901	16	MAX. OPERATING PRESSURE	85 barg
10	MEDIUM	NATURAL GAS	17	OPERATING TEMPERATURE	+5 to +25 °C
11	GAS COMPOSITION	C4G-HPPL-ILF-GENER-GEN-DAT-820	18	DESIGN PRESSURE	100 barg
12	PIPING CLASS	CS100-0	19	DESIGN TEMPERATURE	-20 to +50 °C
13	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	20	TEST PRESSURE	150 barg
14	FLANGE STANDARD / RATING	ASME B16.5 / #600 - RF	21	SAFETY FACTOR (TO YIELD POINT)	2.15
15	INSTALLATION	ABOVEGROUND	22	SAFETY FACTOR ON WELD ENDS (TO YIELD POINT)	N/A
23	VALVE DATA				
24	VALVE BODY / BALL DESIGN	FULLY WELDED BODY	36	SUPPORT LEGS	YES
25	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	37	LIFTING LUGS	YES
26	NOMINAL PIPE SIZE / OD / THICKNESS	DN 300 / 323.9 mm / 8.8 mm	38	FLOW DIRECTION	BIDIRECTIONAL
27	PIPELINE CONNECTION TYPE	FLANGE / FLANGE	39	LEAK RATE	ACC. TO EN 12266-1, -2; RATE A
28	MAIN SEALS	METAL	40	MAX. VALVE LIFT	*
29	SECONDARY SEALS	SOFT	41	STEM DIAMETER / TYPE	* / ANTI-BLOW-OUT
30	SEATS RINGS	DOUBLE PISTON EFFECT	42	LOCK POSITION	YES
31	CAVITY PRESSURE RELIEF VALVE	N/A	43	ADJUSTABLE LIMIT STOP	*
32	DOUBLE BLOCK & BLEED	YES	44	ANTI STATIC DESIGN	YES
33	VENT	YES	45	FIRE SAFE DESIGN	YES
34	DRAIN	YES	46	SEALANT LINE INJECTION MEDIA	4 INDPEDENT GREASE FITTINGS
35	INSULATION	NO	47		
48	ACTUATOR AND ACCESSORIES				
49	ACTUATOR TYPE	MANUAL	61	STROKING TIME TO OPEN (Min./Max.)	N/A
50	MANUFACTURER/ MODEL	*	62	STROKING TIME TO CLOSE (Min./Max.)	N/A
51	GEAR BOX WITH HANDWHEEL	YES	63	LIMIT SWITCH	N/A
52	DESIGN TORQUE FOR ACTUATOR	*	64	POSITIONER MANUFACT / MODEL	*
53	ACTUATOR ATTACHMENT	N/A	65	STEM	*
54	FAIL SAFE POSITION	N/A	66	STEM EXTENSION FOR UNDERGROUND	VALVE CL TO ACTUATOR FLANGE
55	POWER SUPPLY	N/A	67	INSTALLATION	VALVE CL TO GROUND LEVEL
56	IP-CODE	N/A	68	BY-PASS AND AIR-BLEED VALVE	N/A
57	INSULATING CLASS	N/A	69	OIL AND GAS FILTERS	N/A
58	HAZARDOUS AREA	ZONE 1	70	CONTROL UNIT	N/A
59	EXPLOSION PROTECTION	II 2G IIB T3	71	ACTUATOR LOCKING	N/A
60	MINIMUM SUPPLY PRESSURE	N/A	72	MECANICAL POSITION INDICATOR	YES - OPEN/CLOSE
73	DIMENSIONS, WEIGHT, MECHANICAL AND ELECTRICAL INTERFACES				
74	FITTING LENGTH	*	78	WEIGHT (VALVE)	*
75	FITTING HEIGHT	*	79	WEIGHT (VALVE + ACTUATOR)	*
76	WALL THICKNESS	*	80	CABLE CONNECTION TYPE	N/A
77			81	CABLE CONNECTION SIZE	*
82	MATERIALS, TESTING AND DOCUMENTATION				
83	MATERIAL OF PIPE END	L360NE	92	STANDARD TEST	ACC TO CSN EN 14141 / API 6D
84	VALVE MATERIAL	ACC. TO ČSN EN 1594/API 6D	93	LEAKAGE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
85	BALL MATERIAL	C4G-HPPL-ILF-GENER-STR-SPC-824	94	PRESSURE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
86	PUP PIECES MATERIAL	*	95	TIGHTNESS TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
87	MATERIAL STEM	*	96	FIRE SAFE TEST	ACC. TO API 607 / ISO 10497
88	MATERIAL BOLTS / NUTS	ACC. TO ČSN EN ISO 898	97	ATEX CERTIFICATION	ACC. TO CSN EN 60079-10
89	MATERIAL SEAT / SEAL	A350 LF2 / HNBR (Therban) *	98	SAFETY INTEGRITY LEVEL	N/A
90	ANTI - CORROSION PROTECTION	C4G-HPPL-ILF-GENER-STR-SPC-824	99	FINAL ACCEPTANCE TEST	ČSN EN 10204 / 3.2
91	DOCUMENTATION	C4G-HPPL-ILF-GENER-STR-SPC-824	100	CE-CONFORMITY	ACC. TO PED 2014/68/EU
101	NOTES				
102	* To be filled/confirmed by Supplier				
103	Note 1: This data sheet shall be read with the Specification C4G-HPPL-ILF-GENER-STR-SPC-824				
104	Note 2: CL - Center Line				
105	Note 3: N/A - Not Applicable				
106					
107					
108					
109					
110					
111					
112					
113					
114					
115					
116					
117					

BALL VALVE - DN 500					
1	GENERAL INFORMATION				
2	LOCATION	LVS MLADOTICE	5	QUANTITY	2
3	EQUIPMENT	BALL VALVE	6	TECHNICAL SPECIFICATION	C4G-HPPL-ILF-GENER-STR-SPC-824
4	TAG No.	MOV-7.3, MOV-7.4	7	P&ID-No.	C4G-HPPL-ILF-TU40S-STR-DIA-110
8	OPERATION AND DESIGN DATA				
9	AMBIENT CONDITIONS	C4G-HPPL-ILF-GENER-GEN-SPC-901	16	MAX. OPERATING PRESSURE	85 barg
10	MEDIUM	NATURAL GAS	17	OPERATING TEMPERATURE	+5 to +25 °C
11	GAS COMPOSITION	C4G-HPPL-ILF-GENER-GEN-DAT-820	18	DESIGN PRESSURE	100 barg
12	PIPING CLASS	CS100-0	19	DESIGN TEMPERATURE	-20 to +50 °C
13	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	20	TEST PRESSURE	150 barg
14	FLANGE STANDARD / RATING	N/A	21	SAFETY FACTOR (TO YIELD POINT)	2.15
15	INSTALLATION	ABOVEGROUND	22	SAFETY FACTOR ON WELD ENDS (TO YIELD POINT)	1.68
23	VALVE DATA				
24	VALVE BODY / BALL DESIGN	FULLY WELDED BODY	36	SUPPORT LEGS	YES
25	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	37	LIFTING LUGS	YES
26	NOMINAL PIPE SIZE / OD / THICKNESS	DN 500 / 508 mm / 12.5 mm	38	FLOW DIRECTION	BIDIRECTIONAL
27	PIPELINE CONNECTION TYPE	WELD / WELD	39	LEAK RATE	ACC. TO EN 12266-1, -2; RATE A
28	MAIN SEALS	METAL	40	MAX. VALVE LIFT	*
29	SECONDARY SEALS	SOFT	41	STEM DIAMETER / TYPE	* / ANTI-BLOW-OUT
30	SEATS RINGS	DOUBLE PISTON EFFECT	42	LOCK POSITION	YES
31	CAVITY PRESSURE RELIEF VALVE	N/A	43	ADJUSTABLE LIMIT STOP	*
32	DOUBLE BLOCK & BLEED	YES	44	ANTI STATIC DESIGN	YES
33	VENT	YES	45	FIRE SAFE DESIGN	YES
34	DRAIN	YES	46	SEALANT LINE INJECTION MEDIA	4 INDPEDENT GREASE FITTINGS
35	INSULATION	NO	47		
48	ACTUATOR AND ACCESSORIES				
49	ACTUATOR TYPE	ELECTRO MOTOR (Note 2) (Note 6)	61	STROKING TIME TO OPEN (Min./Max.)	40 s/180 s
50	MANUFACTURER/ MODEL	AUMATIC SAEx	62	STROKING TIME TO CLOSE (Min./Max.)	60 s /180 s
51	GEAR BOX WITH HANDWHEEL	N/A	63	LIMIT SWITCH	YES
52	DESIGN TORQUE FOR ACTUATOR	*	64	POSITIONER MANUFACT / MODEL	*
53	ACTUATOR ATTACHMENT	ACC. TO EN ISO 5211	65	STEM	*
54	FAIL SAFE POSITION	N/A	66	STEM EXTENSION FOR UNDERGROUND	VALVE CL TO ACTUATOR FLANGE
55	POWER SUPPLY	400V / 50 Hz / 3 Ph	67	INSTALLATION	VALVE CL TO GROUND LEVEL
56	IP-CODE	IP 65 (IEC 60529)	68	BY-PASS AND AIR-BLEED VALVE	N/A
57	INSULATING CLASS	I	69	OIL AND GAS FILTERS	N/A
58	HAZARDOUS AREA	ZONE 1	70	CONTROL UNIT	C4G-HPPL-ILF-GENER-STR-SPC-824
59	EXPLOSION PROTECTION	II 2G IIB T3	71	ACTUATOR LOCKING	SELF LOCKING
60	MINIMUM SUPPLY PRESSURE	N/A	72	MECHANICAL POSITION INDICATOR	YES - OPEN/CLOSE
73	DIMENSIONS, WEIGHT, MECHANICAL AND ELECTRICAL INTERFACES				
74	FITTING LENGTH	*	78	WEIGHT (VALVE)	*
75	FITTING HEIGHT	*	79	WEIGHT (VALVE + ACTUATOR)	*
76	WALL THICKNESS	*	80	CABLE CONNECTION TYPE	Exd Cable Gland
77			81	CABLE CONNECTION SIZE	*
82	MATERIALS, TESTING AND DOCUMENTATION				
83	MATERIAL OF PIPE END	L360NE	92	STANDARD TEST	ACC TO CSN EN 14141 / API 6D
84	VALVE MATERIAL	ACC. TO ČSN EN 1594/API 6D	93	LEAKAGE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
85	BALL MATERIAL	C4G-HPPL-ILF-GENER-STR-SPC-824	94	PRESSURE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
86	PUP PIECES MATERIAL	*	95	TIGHTNESS TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
87	MATERIAL STEM	*	96	FIRE SAFE TEST	ACC. TO API 607 / ISO 10497
88	MATERIAL BOLTS / NUTS	ACC. TO ČSN EN ISO 898	97	ATEX CERTIFICATION	ACC. TO CSN EN 60079-10
89	MATERIAL SEAT / SEAL	A350 LF2 / HNBR (Therban) *	98	SAFETY INTEGRITY LEVEL	N/A
90	ANTI - CORROSION PROTECTION	C4G-HPPL-ILF-GENER-STR-SPC-824	99	FINAL ACCEPTANCE TEST	ČSN EN 10204 / 3.2
91	DOCUMENTATION	C4G-HPPL-ILF-GENER-STR-SPC-824	100	CE-CONFORMITY	ACC. TO PED 2014/68/EU
101	NOTES				
102	* To be filled/confirmed by Supplier				
103	Note 1: This data sheet shall be read with the Specification C4G-HPPL-ILF-GENER-STR-SPC-824				
104	Note 2: Motor Operated Valve (MOV) with Local and Remote Control and Monitoring Functionality				
105	Note 3: CL - Center Line				
106	Note 4: N/A - Not Applicable				
107	Note 5: Control and Signaling Voltage 24 VDC				
108	Note 6: The type of wiring diagram shall be "TPCAA121D1H1-E460 TPA00R200-012-000"				
109					
110					
111					
112					
113					
114					
115					
116					
117					

BALL VALVE - DN 500					
1	GENERAL INFORMATION				
2	LOCATION	LVS HUBENOV	5	QUANTITY	2
3	EQUIPMENT	BALL VALVE	6	TECHNICAL SPECIFICATION	C4G-HPPL-ILF-GENER-STR-SPC-824
4	TAG No.	MOV-7.3, MOV-7.4	7	P&ID-No.	C4G-HPPL-ILF-TU41S-STR-DIA-110
8	OPERATION AND DESIGN DATA				
9	AMBIENT CONDITIONS	C4G-HPPL-ILF-GENER-GEN-SPC-901	16	MAX. OPERATING PRESSURE	85 barg
10	MEDIUM	NATURAL GAS	17	OPERATING TEMPERATURE	+5 to +25 °C
11	GAS COMPOSITION	C4G-HPPL-ILF-GENER-GEN-DAT-820	18	DESIGN PRESSURE	100 barg
12	PIPING CLASS	CS100-0	19	DESIGN TEMPERATURE	-20 to +50 °C
13	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	20	TEST PRESSURE	150 barg
14	FLANGE STANDARD / RATING	N/A	21	SAFETY FACTOR (TO YIELD POINT)	2.15
15	INSTALLATION	ABOVEGROUND	22	SAFETY FACTOR ON WELD ENDS (TO YIELD POINT)	1.68
23	VALVE DATA				
24	VALVE BODY / BALL DESIGN	FULLY WELDED BODY	36	SUPPORT LEGS	YES
25	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	37	LIFTING LUGS	YES
26	NOMINAL PIPE SIZE / OD / THICKNESS	DN 500 / 508 mm / 12.5 mm	38	FLOW DIRECTION	BIDIRECTIONAL
27	PIPELINE CONNECTION TYPE	WELD / WELD	39	LEAK RATE	ACC. TO EN 12266-1, -2; RATE A
28	MAIN SEALS	METAL	40	MAX. VALVE LIFT	*
29	SECONDARY SEALS	SOFT	41	STEM DIAMETER / TYPE	* / ANTI-BLOW-OUT
30	SEATS RINGS	DOUBLE PISTON EFFECT	42	LOCK POSITION	YES
31	CAVITY PRESSURE RELIEF VALVE	N/A	43	ADJUSTABLE LIMIT STOP	*
32	DOUBLE BLOCK & BLEED	YES	44	ANTI STATIC DESIGN	YES
33	VENT	YES	45	FIRE SAFE DESIGN	YES
34	DRAIN	YES	46	SEALANT LINE INJECTION MEDIA	4 INDPEDENT GREASE FITTINGS
35	INSULATION	NO	47		
48	ACTUATOR AND ACCESSORIES				
49	ACTUATOR TYPE	ELECTRO MOTOR (Note 2) (Note 6)	61	STROKING TIME TO OPEN (Min./Max.)	40 s/180 s
50	MANUFACTURER/ MODEL	AUMATIC SAEx	62	STROKING TIME TO CLOSE (Min./Max.)	60 s /180 s
51	GEAR BOX WITH HANDWHEEL	N/A	63	LIMIT SWITCH	YES
52	DESIGN TORQUE FOR ACTUATOR	*	64	POSITIONER MANUFACT / MODEL	*
53	ACTUATOR ATTACHMENT	ACC. TO EN ISO 5211	65	STEM	*
54	FAIL SAFE POSITION	N/A	66	STEM EXTENSION FOR UNDERGROUND	VALVE CL TO ACTUATOR FLANGE
55	POWER SUPPLY	400V / 50 Hz / 3 Ph	67	INSTALLATION	VALVE CL TO GROUND LEVEL
56	IP-CODE	IP 65 (IEC 60529)	68	BY-PASS AND AIR-BLEED VALVE	N/A
57	INSULATING CLASS	I	69	OIL AND GAS FILTERS	N/A
58	HAZARDOUS AREA	ZONE 1	70	CONTROL UNIT	C4G-HPPL-ILF-GENER-STR-SPC-824
59	EXPLOSION PROTECTION	II 2G IIB T3	71	ACTUATOR LOCKING	SELF LOCKING
60	MINIMUM SUPPLY PRESSURE	N/A	72	MECANICAL POSITION INDICATOR	YES - OPEN/CLOSE
73	DIMENSIONS, WEIGHT, MECHANICAL AND ELECTRICAL INTERFACES				
74	FITTING LENGTH	*	78	WEIGHT (VALVE)	*
75	FITTING HEIGHT	*	79	WEIGHT (VALVE + ACTUATOR)	*
76	WALL THICKNESS	*	80	CABLE CONNECTION TYPE	Exd Cable Gland
77			81	CABLE CONNECTION SIZE	*
82	MATERIALS, TESTING AND DOCUMENTATION				
83	MATERIAL OF PIPE END	L360NE	92	STANDARD TEST	ACC TO CSN EN 14141 / API 6D
84	VALVE MATERIAL	ACC. TO ČSN EN 1594/API 6D	93	LEAKAGE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
85	BALL MATERIAL	C4G-HPPL-ILF-GENER-STR-SPC-824	94	PRESSURE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
86	PUP PIECES MATERIAL	*	95	TIGHTNESS TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
87	MATERIAL STEM	*	96	FIRE SAFE TEST	ACC. TO API 607 / ISO 10497
88	MATERIAL BOLTS / NUTS	ACC. TO ČSN EN ISO 898	97	ATEX CERTIFICATION	ACC. TO CSN EN 60079-10
89	MATERIAL SEAT / SEAL	A350 LF2 / HNBR (Therban) *	98	SAFETY INTEGRITY LEVEL	N/A
90	ANTI - CORROSION PROTECTION	C4G-HPPL-ILF-GENER-STR-SPC-824	99	FINAL ACCEPTANCE TEST	ČSN EN 10204 / 3.2
91	DOCUMENTATION	C4G-HPPL-ILF-GENER-STR-SPC-824	100	CE-CONFORMITY	ACC. TO PED 2014/68/EU
101	NOTES				
102	* To be filled/confirmed by Supplier				
103	Note 1: This data sheet shall be read with the Specification C4G-HPPL-ILF-GENER-STR-SPC-824				
104	Note 2: Motor Operated Valve (MOV) with Local and Remote Control and Monitoring Functionality				
105	Note 3: CL - Center Line				
106	Note 4: N/A - Not Applicable				
107	Note 5: Control and Signaling Voltage 24 VDC				
108	Note 6: The type of wiring diagram shall be "TPCAA121D1H1-E460 TPA00R200-012-000"				
109					
110					
111					
112					
113					
114					
115					
116					
117					

BALL VALVE - DN 500					
1	GENERAL INFORMATION				
2	LOCATION	LVS SVINOMAZY	5	QUANTITY	2
3	EQUIPMENT	BALL VALVE	6	TECHNICAL SPECIFICATION	C4G-HPPL-ILF-GENER-STR-SPC-824
4	TAG No.	MOV-7.25, MOV-7.26	7	P&ID-No.	C4G-HPPL-ILF-TU42S-STR-DIA-110
8	OPERATION AND DESIGN DATA				
9	AMBIENT CONDITIONS	C4G-HPPL-ILF-GENER-GEN-SPC-901	16	MAX. OPERATING PRESSURE	85 barg
10	MEDIUM	NATURAL GAS	17	OPERATING TEMPERATURE	+5 to +25 °C
11	GAS COMPOSITION	C4G-HPPL-ILF-GENER-GEN-DAT-820	18	DESIGN PRESSURE	100 barg
12	PIPING CLASS	CS100-0	19	DESIGN TEMPERATURE	-20 to +50 °C
13	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	20	TEST PRESSURE	150 barg
14	FLANGE STANDARD / RATING	N/A	21	SAFETY FACTOR (TO YIELD POINT)	2.15
15	INSTALLATION	ABOVEGROUND	22	SAFETY FACTOR ON WELD ENDS (TO YIELD POINT)	1.68
23	VALVE DATA				
24	VALVE BODY / BALL DESIGN	FULLY WELDED BODY	36	SUPPORT LEGS	YES
25	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	37	LIFTING LUGS	YES
26	NOMINAL PIPE SIZE / OD / THICKNESS	DN 500 / 508 mm / 12.5 mm	38	FLOW DIRECTION	BIDIRECTIONAL
27	PIPELINE CONNECTION TYPE	WELD / WELD	39	LEAK RATE	ACC. TO EN 12266-1, -2; RATE A
28	MAIN SEALS	METAL	40	MAX. VALVE LIFT	*
29	SECONDARY SEALS	SOFT	41	STEM DIAMETER / TYPE	* / ANTI-BLOW-OUT
30	SEATS RINGS	DOUBLE PISTON EFFECT	42	LOCK POSITION	YES
31	CAVITY PRESSURE RELIEF VALVE	N/A	43	ADJUSTABLE LIMIT STOP	*
32	DOUBLE BLOCK & BLEED	YES	44	ANTI STATIC DESIGN	YES
33	VENT	YES	45	FIRE SAFE DESIGN	YES
34	DRAIN	YES	46	SEALANT LINE INJECTION MEDIA	4 INDPEDENT GREASE FITTINGS
35	INSULATION	NO	47		
48	ACTUATOR AND ACCESSORIES				
49	ACTUATOR TYPE	ELECTRO MOTOR (Note 2) (Note 6)	61	STROKING TIME TO OPEN (Min./Max.)	40 s/180 s
50	MANUFACTURER/ MODEL	AUMATIC SAEx	62	STROKING TIME TO CLOSE (Min./Max.)	60 s /180 s
51	GEAR BOX WITH HANDWHEEL	N/A	63	LIMIT SWITCH	YES
52	DESIGN TORQUE FOR ACTUATOR	*	64	POSITIONER MANUFACT / MODEL	*
53	ACTUATOR ATTACHMENT	ACC. TO EN ISO 5211	65	STEM	*
54	FAIL SAFE POSITION	N/A	66	STEM EXTENSION FOR UNDERGROUND	VALVE CL TO ACTUATOR FLANGE
55	POWER SUPPLY	400V / 50 Hz / 3 Ph	67	INSTALLATION	VALVE CL TO GROUND LEVEL
56	IP-CODE	IP 65 (IEC 60529)	68	BY-PASS AND AIR-BLEED VALVE	N/A
57	INSULATING CLASS	I	69	OIL AND GAS FILTERS	N/A
58	HAZARDOUS AREA	ZONE 1	70	CONTROL UNIT	C4G-HPPL-ILF-GENER-STR-SPC-824
59	EXPLOSION PROTECTION	II 2G IIB T3	71	ACTUATOR LOCKING	SELF LOCKING
60	MINIMUM SUPPLY PRESSURE	N/A	72	MECHANICAL POSITION INDICATOR	YES - OPEN/CLOSE
73	DIMENSIONS, WEIGHT, MECHANICAL AND ELECTRICAL INTERFACES				
74	FITTING LENGTH	*	78	WEIGHT (VALVE)	*
75	FITTING HEIGHT	*	79	WEIGHT (VALVE + ACTUATOR)	*
76	WALL THICKNESS	*	80	CABLE CONNECTION TYPE	Exd Cable Gland
77			81	CABLE CONNECTION SIZE	*
82	MATERIALS, TESTING AND DOCUMENTATION				
83	MATERIAL OF PIPE END	L360NE	92	STANDARD TEST	ACC TO CSN EN 14141 / API 6D
84	VALVE MATERIAL	ACC. TO ČSN EN 1594/API 6D	93	LEAKAGE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
85	BALL MATERIAL	C4G-HPPL-ILF-GENER-STR-SPC-824	94	PRESSURE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
86	PUP PIECES MATERIAL	*	95	TIGHTNESS TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
87	MATERIAL STEM	*	96	FIRE SAFE TEST	ACC. TO API 607 / ISO 10497
88	MATERIAL BOLTS / NUTS	ACC. TO ČSN EN ISO 898	97	ATEX CERTIFICATION	ACC. TO CSN EN 60079-10
89	MATERIAL SEAT / SEAL	A350 LF2 / HNBR (Therban) *	98	SAFETY INTEGRITY LEVEL	N/A
90	ANTI - CORROSION PROTECTION	C4G-HPPL-ILF-GENER-STR-SPC-824	99	FINAL ACCEPTANCE TEST	ČSN EN 10204 / 3.2
91	DOCUMENTATION	C4G-HPPL-ILF-GENER-STR-SPC-824	100	CE-CONFORMITY	ACC. TO PED 2014/68/EU
101	NOTES				
102	* To be filled/confirmed by Supplier				
103	Note 1: This data sheet shall be read with the Specification C4G-HPPL-ILF-GENER-STR-SPC-824				
104	Note 2: Motor Operated Valve (MOV) with Local and Remote Control and Monitoring Functionality				
105	Note 3: CL - Center Line				
106	Note 4: N/A - Not Applicable				
107	Note 5: Control and Signaling Voltage 24 VDC				
108	Note 6: The type of wiring diagram shall be "TPCAA121D1H1-E460 TPA00R200-012-000"				
109					
110					
111					
112					
113					
114					
115					
116					
117					

BALL VALVE - DN 500

1	GENERAL INFORMATION				
2	LOCATION	LVS BOR	5	QUANTITY	2
3	EQUIPMENT	BALL VALVE	6	TECHNICAL SPECIFICATION	C4G-HPPL-ILF-GENER-STR-SPC-824
4	TAG No.	MOV-7.3, MOV-7.4	7	P&ID-No.	C4G-HPPL-ILF-TU48S-STR-DIA-110
8	OPERATION AND DESIGN DATA				
9	AMBIENT CONDITIONS	C4G-HPPL-ILF-GENER-GEN-SPC-901	16	MAX. OPERATING PRESSURE	85 barg
10	MEDIUM	NATURAL GAS	17	OPERATING TEMPERATURE	+5 to +25 °C
11	GAS COMPOSITION	C4G-HPPL-ILF-GENER-GEN-DAT-820	18	DESIGN PRESSURE	100 barg
12	PIPING CLASS	CS100-0	19	DESIGN TEMPERATURE	-20 to +50 °C
13	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	20	TEST PRESSURE	150 barg
14	FLANGE STANDARD / RATING	N/A	21	SAFETY FACTOR (TO YIELD POINT)	2.15
15	INSTALLATION	ABOVEGROUND	22	SAFETY FACTOR ON WELD ENDS (TO YIELD POINT)	1.68
23	VALVE DATA				
24	VALVE BODY / BALL DESIGN	FULLY WELDED BODY	36	SUPPORT LEGS	YES
25	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	37	LIFTING LUGS	YES
26	NOMINAL PIPE SIZE / OD / THICKNESS	DN 500 / 508 mm / 12.5 mm	38	FLOW DIRECTION	BIDIRECTIONAL
27	PIPELINE CONNECTION TYPE	WELD / WELD	39	LEAK RATE	ACC. TO EN 12266-1, -2; RATE A
28	MAIN SEALS	METAL	40	MAX. VALVE LIFT	*
29	SECONDARY SEALS	SOFT	41	STEM DIAMETER / TYPE	* / ANTI-BLOW-OUT
30	SEATS RINGS	DOUBLE PISTON EFFECT	42	LOCK POSITION	YES
31	CAVITY PRESSURE RELIEF VALVE	N/A	43	ADJUSTABLE LIMIT STOP	*
32	DOUBLE BLOCK & BLEED	YES	44	ANTI STATIC DESIGN	YES
33	VENT	YES	45	FIRE SAFE DESIGN	YES
34	DRAIN	YES	46	SEALANT LINE INJECTION MEDIA	4 INDPEDENT GREASE FITTINGS
35	INSULATION	NO	47		
48	ACTUATOR AND ACCESSORIES				
49	ACTUATOR TYPE	ELECTRO MOTOR (Note 2) (Note 6)	61	STROKING TIME TO OPEN (Min./Max.)	40 s/180 s
50	MANUFACTURER/ MODEL	AUMATIC SAEx	62	STROKING TIME TO CLOSE (Min./Max.)	60 s /180 s
51	GEAR BOX WITH HANDWHEEL	N/A	63	LIMIT SWITCH	YES
52	DESIGN TORQUE FOR ACTUATOR	*	64	POSITIONER MANUFACT / MODEL	*
53	ACTUATOR ATTACHMENT	ACC. TO EN ISO 5211	65	STEM	*
54	FAIL SAFE POSITION	N/A	66	STEM EXTENSION FOR UNDERGROUND	VALVE CL TO ACTUATOR FLANGE
55	POWER SUPPLY	400V / 50 Hz / 3 Ph	67	INSTALLATION	VALVE CL TO GROUND LEVEL
56	IP-CODE	IP 65 (IEC 60529)	68	BY-PASS AND AIR-BLEED VALVE	N/A
57	INSULATING CLASS	I	69	OIL AND GAS FILTERS	N/A
58	HAZARDOUS AREA	ZONE 1	70	CONTROL UNIT	C4G-HPPL-ILF-GENER-STR-SPC-824
59	EXPLOSION PROTECTION	II 2G IIB T3	71	ACTUATOR LOCKING	SELF LOCKING
60	MINIMUM SUPPLY PRESSURE	N/A	72	MECANICAL POSITION INDICATOR	YES - OPEN/CLOSE
73	DIMENSIONS, WEIGHT, MECHANICAL AND ELECTRICAL INTERFACES				
74	FITTING LENGTH	*	78	WEIGHT (VALVE)	*
75	FITTING HEIGHT	*	79	WEIGHT (VALVE + ACTUATOR)	*
76	WALL THICKNESS	*	80	CABLE CONNECTION TYPE	Exd Cable Gland
77			81	CABLE CONNECTION SIZE	*
82	MATERIALS, TESTING AND DOCUMENTATION				
83	MATERIAL OF PIPE END	L360NE	92	STANDARD TEST	ACC TO CSN EN 14141 / API 6D
84	VALVE MATERIAL	ACC. TO ČSN EN 1594/API 6D	93	LEAKAGE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
85	BALL MATERIAL	C4G-HPPL-ILF-GENER-STR-SPC-824	94	PRESSURE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
86	PUP PIECES MATERIAL	*	95	TIGHTNESS TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
87	MATERIAL STEM	*	96	FIRE SAFE TEST	ACC. TO API 607 / ISO 10497
88	MATERIAL BOLTS / NUTS	ACC. TO ČSN EN ISO 898	97	ATEX CERTIFICATION	ACC. TO CSN EN 60079-10
89	MATERIAL SEAT / SEAL	A350 LF2 / HNBR (Therban) *	98	SAFETY INTEGRITY LEVEL	N/A
90	ANTI - CORROSION PROTECTION	C4G-HPPL-ILF-GENER-STR-SPC-824	99	FINAL ACCEPTANCE TEST	ČSN EN 10204 / 3.2
91	DOCUMENTATION	C4G-HPPL-ILF-GENER-STR-SPC-824	100	CE-CONFORMITY	ACC. TO PED 2014/68/EU
101	NOTES				
102	* To be filled/confirmed by Supplier				
103	Note 1: This data sheet shall be read with the Specification C4G-HPPL-ILF-GENER-STR-SPC-824				
104	Note 2: Motor Operated Valve (MOV) with Local and Remote Control and Monitoring Functionality				
105	Note 3: CL - Center Line				
106	Note 4: N/A - Not Applicable				
107	Note 5: Control and Signaling Voltage 24 VDC				
108	Note 6: The type of wiring diagram shall be "TPCAA121D1H1-E460 TPA00R200-012-000"				
109					
110					
111					
112					
113					
114					
115					
116					
117					

BALL VALVE - DN 300					
1	GENERAL INFORMATION				
2	LOCATION	RU PRIMDA	5	QUANTITY	1
3	EQUIPMENT	BALL VALVE	6	TECHNICAL SPECIFICATION	C4G-HPPL-ILF-GENER-STR-SPC-824
4	TAG No.	MOV-8.33	7	P&ID-No.	C4G-HPPL-ILF-RU005-STR-DIA-110
8	OPERATION AND DESIGN DATA				
9	AMBIENT CONDITIONS	C4G-HPPL-ILF-GENER-GEN-SPC-901	16	MAX. OPERATING PRESSURE	85 barg
10	MEDIUM	NATURAL GAS	17	OPERATING TEMPERATURE	+5 to +25 °C
11	GAS COMPOSITION	C4G-HPPL-ILF-GENER-GEN-DAT-820	18	DESIGN PRESSURE	100 barg
12	PIPING CLASS	CS100-0	19	DESIGN TEMPERATURE	-20 to +50 °C
13	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	20	TEST PRESSURE	150 barg
14	FLANGE STANDARD / RATING	N/A	21	SAFETY FACTOR (TO YIELD POINT)	2.15
15	INSTALLATION	ABOVEGROUND	22	SAFETY FACTOR ON WELD ENDS (TO YIELD POINT)	1.68
23	VALVE DATA				
24	VALVE BODY / BALL DESIGN	FULLY WELDED BODY	36	SUPPORT LEGS	YES
25	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	37	LIFTING LUGS	YES
26	NOMINAL PIPE SIZE / OD / THICKNESS	DN 300 / 323.9 mm / 8.8 mm	38	FLOW DIRECTION	BIDIRECTIONAL
27	PIPELINE CONNECTION TYPE	WELD / WELD	39	LEAK RATE	ACC. TO EN 12266-1, -2; RATE A
28	MAIN SEALS	METAL	40	MAX. VALVE LIFT	*
29	SECONDARY SEALS	SOFT	41	STEM DIAMETER / TYPE	* / ANTI-BLOW-OUT
30	SEATS RINGS	DOUBLE PISTON EFFECT	42	LOCK POSITION	YES
31	CAVITY PRESSURE RELIEF VALVE	N/A	43	ADJUSTABLE LIMIT STOP	*
32	DOUBLE BLOCK & BLEED	YES	44	ANTI STATIC DESIGN	YES
33	VENT	YES	45	FIRE SAFE DESIGN	YES
34	DRAIN	YES	46	SEALANT LINE INJECTION MEDIA	4 INDPEDENT GREASE FITTINGS
35	INSULATION	NO	47		
48	ACTUATOR AND ACCESSORIES				
49	ACTUATOR TYPE	ELECTRO MOTOR (Note 2) (Note 6)	61	STROKING TIME TO OPEN (Min./Max.)	40 s/180 s
50	MANUFACTURER/ MODEL	AUMATIC SAEx	62	STROKING TIME TO CLOSE (Min./Max.)	60 s /180 s
51	GEAR BOX WITH HANDWHEEL	N/A	63	LIMIT SWITCH	YES
52	DESIGN TORQUE FOR ACTUATOR	*	64	POSITIONER MANUFACT / MODEL	*
53	ACTUATOR ATTACHMENT	ACC. TO EN ISO 5211	65	STEM	*
54	FAIL SAFE POSITION	N/A	66	STEM EXTENSION FOR UNDERGROUND	VALVE CL TO ACTUATOR FLANGE
55	POWER SUPPLY	400V / 50 Hz / 3 Ph	67	INSTALLATION	VALVE CL TO GROUND LEVEL
56	IP-CODE	IP 65 (IEC 60529)	68	BY-PASS AND AIR-BLEED VALVE	N/A
57	INSULATING CLASS	I	69	OIL AND GAS FILTERS	N/A
58	HAZARDOUS AREA	ZONE 1	70	CONTROL UNIT	C4G-HPPL-ILF-GENER-STR-SPC-824
59	EXPLOSION PROTECTION	II 2G IIB T3	71	ACTUATOR LOCKING	SELF LOCKING
60	MINIMUM SUPPLY PRESSURE	N/A	72	MECHANICAL POSITION INDICATOR	YES - OPEN/CLOSE
73	DIMENSIONS, WEIGHT, MECHANICAL AND ELECTRICAL INTERFACES				
74	FITTING LENGTH	*	78	WEIGHT (VALVE)	*
75	FITTING HEIGHT	*	79	WEIGHT (VALVE + ACTUATOR)	*
76	WALL THICKNESS	*	80	CABLE CONNECTION TYPE	Exd Cable Gland
77			81	CABLE CONNECTION SIZE	*
82	MATERIALS, TESTING AND DOCUMENTATION				
83	MATERIAL OF PIPE END	L360NE	92	STANDARD TEST	ACC TO CSN EN 14141 / API 6D
84	VALVE MATERIAL	ACC. TO ČSN EN 1594/API 6D	93	LEAKAGE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
85	BALL MATERIAL	C4G-HPPL-ILF-GENER-STR-SPC-824	94	PRESSURE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
86	PUP PIECES MATERIAL	*	95	TIGHTNESS TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
87	MATERIAL STEM	*	96	FIRE SAFE TEST	ACC. TO API 607 / ISO 10497
88	MATERIAL BOLTS / NUTS	ACC. TO ČSN EN ISO 898	97	ATEX CERTIFICATION	ACC. TO CSN EN 60079-10
89	MATERIAL SEAT / SEAL	A350 LF2 / HNBR (Therban) *	98	SAFETY INTEGRITY LEVEL	N/A
90	ANTI - CORROSION PROTECTION	C4G-HPPL-ILF-GENER-STR-SPC-824	99	FINAL ACCEPTANCE TEST	ČSN EN 10204 / 3.2
91	DOCUMENTATION	C4G-HPPL-ILF-GENER-STR-SPC-824	100	CE-CONFORMITY	ACC. TO PED 2014/68/EU
101	NOTES				
102	* To be filled/confirmed by Supplier				
103	Note 1: This data sheet shall be read with the Specification C4G-HPPL-ILF-GENER-STR-SPC-824				
104	Note 2: Motor Operated Valve (MOV) with Local Control and Monitoring				
105	Note 3: CL - Center Line				
106	Note 4: N/A - Not Applicable				
107	Note 5: Control and Signaling Voltage 24 VDC				
108	Note 6: The type of wiring diagram shall be "TPCAA121D1H1-E460 TPA00R200-012-000"				
109					
110					
111					
112					
113					
114					
115					
116					
117					

BALL VALVE - DN 300					
1	GENERAL INFORMATION				
2	LOCATION	RU PRIMDA	5	QUANTITY	1
3	EQUIPMENT	BALL VALVE	6	TECHNICAL SPECIFICATION	C4G-HPPL-ILF-GENER-STR-SPC-824
4	TAG No.	8.34	7	P&ID-No.	C4G-HPPL-ILF-RU005-STR-DIA-110
8	OPERATION AND DESIGN DATA				
9	AMBIENT CONDITIONS	C4G-HPPL-ILF-GENER-GEN-SPC-901	16	MAX. OPERATING PRESSURE	85 barg
10	MEDIUM	NATURAL GAS	17	OPERATING TEMPERATURE	+5 to +25 °C
11	GAS COMPOSITION	C4G-HPPL-ILF-GENER-GEN-DAT-820	18	DESIGN PRESSURE	100 barg
12	PIPING CLASS	CS100-0	19	DESIGN TEMPERATURE	-20 to +50 °C
13	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	20	TEST PRESSURE	150 barg
14	FLANGE STANDARD / RATING	ASME B16.5 / #600 - RF	21	SAFETY FACTOR (TO YIELD POINT)	2.15
15	INSTALLATION	ABOVEGROUND	22	SAFETY FACTOR ON WELD ENDS (TO YIELD POINT)	N/A
23	VALVE DATA				
24	VALVE BODY / BALL DESIGN	FULLY WELDED BODY	36	SUPPORT LEGS	YES
25	DESIGN STANDARD	CSN EN 13942 / API 6D / ISO 14313	37	LIFTING LUGS	YES
26	NOMINAL PIPE SIZE / OD / THICKNESS	DN 300 / 323.9 mm / 8.8 mm	38	FLOW DIRECTION	BIDIRECTIONAL
27	PIPELINE CONNECTION TYPE	FLANGE / FLANGE	39	LEAK RATE	ACC. TO EN 12266-1, -2; RATE A
28	MAIN SEALS	METAL	40	MAX. VALVE LIFT	*
29	SECONDARY SEALS	SOFT	41	STEM DIAMETER / TYPE	* / ANTI-BLOW-OUT
30	SEATS RINGS	DOUBLE PISTON EFFECT	42	LOCK POSITION	YES
31	CAVITY PRESSURE RELIEF VALVE	N/A	43	ADJUSTABLE LIMIT STOP	*
32	DOUBLE BLOCK & BLEED	YES	44	ANTI STATIC DESIGN	YES
33	VENT	YES	45	FIRE SAFE DESIGN	YES
34	DRAIN	YES	46	SEALANT LINE INJECTION MEDIA	4 INDPEDENT GREASE FITTINGS
35	INSULATION	NO	47		
48	ACTUATOR AND ACCESSORIES				
49	ACTUATOR TYPE	MANUAL	61	STROKING TIME TO OPEN (Min./Max.)	N/A
50	MANUFACTURER/ MODEL	*	62	STROKING TIME TO CLOSE (Min./Max.)	N/A
51	GEAR BOX WITH HANDWHEEL	YES	63	LIMIT SWITCH	N/A
52	DESIGN TORQUE FOR ACTUATOR	*	64	POSITIONER MANUFACT / MODEL	*
53	ACTUATOR ATTACHMENT	N/A	65	STEM	*
54	FAIL SAFE POSITION	N/A	66	STEM EXTENSION FOR UNDERGROUND	VALVE CL TO ACTUATOR FLANGE
55	POWER SUPPLY	N/A	67	INSTALLATION	VALVE CL TO GROUND LEVEL
56	IP-CODE	N/A	68	BY-PASS AND AIR-BLEED VALVE	N/A
57	INSULATING CLASS	N/A	69	OIL AND GAS FILTERS	N/A
58	HAZARDOUS AREA	ZONE 1	70	CONTROL UNIT	N/A
59	EXPLOSION PROTECTION	II 2G IIB T3	71	ACTUATOR LOCKING	N/A
60	MINIMUM SUPPLY PRESSURE	N/A	72	MECANICAL POSITION INDICATOR	YES - OPEN/CLOSE
73	DIMENSIONS, WEIGHT, MECHANICAL AND ELECTRICAL INTERFACES				
74	FITTING LENGTH	*	78	WEIGHT (VALVE)	*
75	FITTING HEIGHT	*	79	WEIGHT (VALVE + ACTUATOR)	*
76	WALL THICKNESS	*	80	CABLE CONNECTION TYPE	N/A
77			81	CABLE CONNECTION SIZE	*
82	MATERIALS, TESTING AND DOCUMENTATION				
83	MATERIAL OF PIPE END	L360NE	92	STANDARD TEST	ACC TO CSN EN 14141 / API 6D
84	VALVE MATERIAL	ACC. TO ČSN EN 1594/API 6D	93	LEAKAGE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
85	BALL MATERIAL	C4G-HPPL-ILF-GENER-STR-SPC-824	94	PRESSURE TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
86	PUP PIECES MATERIAL	*	95	TIGHTNESS TEST	C4G-HPPL-ILF-GENER-STR-SPC-824 (TABLE III)
87	MATERIAL STEM	*	96	FIRE SAFE TEST	ACC. TO API 607 / ISO 10497
88	MATERIAL BOLTS / NUTS	ACC. TO ČSN EN ISO 898	97	ATEX CERTIFICATION	ACC. TO CSN EN 60079-10
89	MATERIAL SEAT / SEAL	A350 LF2 / HNBR (Therban) *	98	SAFETY INTEGRITY LEVEL	N/A
90	ANTI - CORROSION PROTECTION	C4G-HPPL-ILF-GENER-STR-SPC-824	99	FINAL ACCEPTANCE TEST	ČSN EN 10204 / 3.2
91	DOCUMENTATION	C4G-HPPL-ILF-GENER-STR-SPC-824	100	CE-CONFORMITY	ACC. TO PED 2014/68/EU
101	NOTES				
102	* To be filled/confirmed by Supplier				
103	Note 1: This data sheet shall be read with the Specification C4G-HPPL-ILF-GENER-STR-SPC-824				
104	Note 2: CL - Center Line				
105	Note 3: N/A - Not Applicable				
106					
107					
108					
109					
110					
111					
112					
113					
114					
115					
116					
117					