



OPREDELITEV VARNOSTI		VARNOSTI		VARNOSTI		VARNOSTI	
problema	profili	deležina	kg/m	ks	homotnost [kg]	poz	o-3
1	R12	2,50	0,888	30,00	66,60	26,40	R.V.
2	R12	1,60	0,888	77,00	102,30	26,40	R.V.
3	R12	1,30	0,888	100,00	117,75	26,40	R.V.
6	R10	3,70	0,617	56,00	112,74	26,40	R.V.
7	R12	1,40	0,888	100,00	174,05	26,40	R.V.
8	R10	10,00	0,617	44,00	271,48	26,40	R.V.
9	R10	2,25	0,617	40,00	55,33	26,40	R.V.
10	R10	4,00	0,617	66,00	162,89	26,40	R.V.
CELKOMA							
					107,43		

- DRÍK STĚNY NAVRŽEN Z TVÁRNIC ZTRACENÉHO BEDNĚNÍ 350/250
- PRAC. SPÁRA BUDE OCHRÁNĚNA NÁBĚHOVÝM KLÍNEM (150/150mm) PRO IZOLACI

BETON C25/30 XA1 - 22,5 m3

VÝŠKA DESKY - 350mm

VÝZTUŽ R10505 (B500)

KRYTÍ DESKY 4,5 mm

KRYTÍ STĚNY 25 mm

[illegible]